

FLECK 9000 - TWIN

DESCRIPTION

9000 is a lead-free brass valve with fully adjustable 5-cycle control for efficient and reliable water treatment and backwash capabilities accommodating softener tanks up to 16". It regenerates immediately when needed for continuous soft water, keeping system clean for optimum operating efficiency and minimum maintenance.



FEATURES

- Regenerates with soft water
- Choice of 3/4" or 1" meter
- Use of 100% of tank capacity before switching to the second tank
- Backwash capability handles up to 16" diameter tanks

VALVE SPECIFICATIONS

| | |
|--------------------|-------------------------|
| Service flow rate | 4.00 m ³ /hr |
| Backwash flow rate | 1.90 m ³ /hr |
| Operating pressure | 1.4 to 8.5 bar |
| Water temperature | 1°C to 43°C |
| Valve material | Brass |
| In/out | 3/4 inch or 1 inch |
| Type timer | SXT |
| Hot water | No |

*3.5 bar inlet - valve alone

ELECTRONIC VALVES*

| REFERENCE | CONFIG | SEARCH NAME | ITEM NAME |
|------------|---------|-------------|--|
| 0301900103 | SXT03 | V900SI-602 | Fleck 9000/1600 SXT Twin Duplex Eco SXT 3/4" 1/2,4/0,5 |
| 0301900103 | DSXD 1" | V900SI-604 | Fleck 9000/1600 SXT Twin Duplex Eco SXT 1" 2/2,4/0,5 |

Flexible hoses (WRAS approved)

| | | |
|------------|--------------|-------------------------------------|
| 2705000001 | 25SW0250FF01 | 250mm 1" Female BSP Flexible Hose |
| 2705000002 | 25SW0300FF01 | 300mm 1" Female BSP Flexible Hose |
| 2705000003 | 25SW0350FF01 | 350mm 1" Female BSP Flexible Hose |
| 2705000004 | 25SW0400FF01 | 400mm 1" Female BSP Flexible Hose |
| 0401358419 | 18706-10 | Yoke for Hoses (2 per set required) |

All valves are equipped with a transformer, top distributors, drain elbow, 2nd tank adapter
Yokes/ Bypass/ Aircheck / Distributor tube/ Bottom distributor are not included in the prices and must be ordered separately.