

# FLECK 9500 - TWIN

## DESCRIPTION

9500 is a lead-free brass valve with fully adjustable 5-cycle control for efficient and reliable water treatment and backwash capabilities accommodating softener tanks up to 24". It regenerates immediately when needed for continuous soft water, keeping system clean for optimum operating efficiency and minimum maintenance.



## FEATURES

- Regenerates with soft water
- Backwash capability handles up to 24" tanks
- 100% capacity use of the tank in service before switching to the second tank
- Service flow rate: up to 8,4 m<sup>3</sup>/h

## VALVE SPECIFICATIONS

Service flow rate	8.4 m <sup>3</sup> /hr
Backwash flow rate	3.30 m <sup>3</sup> /hr
Operating pressure	1.4 to 8.5 bar
Water temperature	1°C to 43°C
Valve material	Brass
In/out	1.5 inch
Type timer	SXT
Hot water	No

\*3.5 bar inlet - valve alone

## ELECTRONIC VALVES\*

REFERENCE	CONFIG	SEARCH NAME	ITEM NAME
0301950105	DSX64D	V950SI-600	Fleck 9500/1650 SXT Twin   Duplex SXT Eco 1"1/2   3/5/1
0301950106	DSX64D	V950SI-600	Fleck 9500/1710 SXT Twin   Duplex SXT Eco 1"1/2   4C/15/2

### Kit copper tubes 2nd tank adapter

0401298277		28137-16	Tube Connector 16" 9500 Assy
0401298278		28137-20	Tube Connector 20" 9500 Assy
0401298279		28137-24	Tube Connector 24" 9500 Assy

All valves are equipped with a transformer, top distributors, drain elbow, 2nd tank adapter  
Yokes/ Bypass/ Aircheck / Distributor tube/ Bottom distributor are not included in the prices and must be ordered separately.