FLECK 2750

DESCRIPTION

2750 is a lead-free brass valve ensuring a superior strength and durability with continuous service flow rate of 98 l/min with a backwash of 94 l/min. Ideal for residential or commercial filter and softener applications.



FEATURES

- Time-tested, hydraulically-balanced piston, seal and spacer concept
- Regeneration: electronical
- Valve body in brass
- Can be fitted on pressure vessels up to 24"

VALVE SPECIFICATIONS

Service flow rate	5.9 m³/hr
Backwash flow rate	5.6 m ³ /hr
Operating pressure	1.4 to 8.5 bar
Water temperature	1°C to 43°C
Valve material	Brass
In/out	1 inch
Type timer	SXT
Hot water	Mechanical & NXT2

^{*3.5} bar inlet - valve alone

FLECK 2750



ELECTRONIC VALVES & METERS*

REFERENCE	CONFIG	SEARCH NAME	ITEM NAME
0301270097	CSXD	V275SC-603	Fleck 2750/1650 SXT Chrono SXT Down Flow 3/5/1
Electronic meters			
0401150022		29096	Kit 1" Meter NXT Stainless Steel

FILTER VALVES & DLFC'S*

REFERENCE	CONFIG	SEARCH NAME	ITEM NAME	
0301276108	SXT	V275SC-600	Fleck 2750 Filter Chrono SXT - no DLFC	
0301276108	SXT-NB	V275SC-601	Fleck 2750 Filter Chrono SXT NBP - no DLFC	
0301276108	SXT-NBHW	V275SC-602	Fleck 2750 Filter Chrono SXT Hot Water NBP - no DLFC	
DLFC's				
0401036507		24212*	DLFC ¾" NPT - ½" NPT 1,2 - 7 GPM 2750	
0401036506		24202*	DLFC 3/4" NPT - 3/4" BSP 9 - 25GPM 2750	

^{*}Filter versions: DLFC to be ordered separately

^{*}Electronic versions: meter to be ordered separately