

FLECK 5600SXT

DESCRIPTION

5600 SXT is a high performance control valve with multiple options for softener applications. Its backwash capabilities perfectly accommodate softener tanks up to 12" in diameter. Two non-corrosive, UV-resistant, fiber-reinforced noryl valve body designs are proposed: one for downflow regeneration and one for upflow (covers every valve in the 5600 family - quick access to all internal components). The valve is user-friendly, easily programmable and its modular design simplifies the disassembly and the maintenance.



FEATURES

- Large backlit LCD display with 3 push buttons
- Advanced programming with 6 adjustable cycle times
- Service flow rate up to 4.5m³
- Valve body in reinforced Noryl

VALVE SPECIFICATIONS

| | |
|--------------------|------------------------|
| Service flow rate | 4.5 m ³ /hr |
| Backwash flow rate | 1.6 m ³ /hr |
| Operating pressure | 1.4 to 8.5 bar |
| Water temperature | 1°C to 43°C |
| Valve material | Noryl |
| In/out | 3/4 inch or 1 inch |
| Type timer | SXT |
| Hot water | No |

*3.5 bar inlet - valve alone

VALVES

| REFERENCE | CONFIG | SEARCH NAME | ITEM NAME |
|------------|--------|-------------|--|
| 0301561549 | CSXD02 | V560SC601 | Fleck 5600 SXT Chrono SXT Down Flow 1/1,5/0,25 |
| 0301561549 | ESXD05 | V560X6 | Fleck 5600 SXT Eco SXT Down Flow 0/1.5/0.25 |

DO YOU NEED A YOKE?

FILTER VERSION NOT AVAILABLE ANYMORE

All valves are equipped with a transformer and a top distributor
Yokes/ Bypass/ Aircheck / Distributor tube and Bottom distributor are not included in the prices and must be ordered separately.