

PWG MEMBRANE HOUSINGS

DESCRIPTION

PWG membrane housings are engineered for use in Reverse Osmosis systems for a variety of applications with pressures up to 1,200 PSI. The pressure vessels are designed to accommodate any standard made 2.5", 4" and 8".



APPLICATION

- Reverse Osmosis
- Industrial Water Treatment
- Commercial Water Treatment
- Applications with pressures up to 1200 PSI

BENEFITS

- Designed to provide a long-term, trouble-free operation with minimal downtime
- Accurate temperature flow curing process
- UV resistant polyurethane exterior paint finish
- Designed for small and large applications
- Large stock, quick delivery
- Certified quality control

REFERENCE	ITEM NAME	DIAMETER INCH	LENGTH	PRESSURE PSI	PORT POSITION	
1215010001	2514 EP	2.5	14"	300	EP	
1215010002	2521 EP	2.5	21"	300	EP	
1215010003	2540 EP	2.5	40"	300	EP	
1215020001	4021 EP	4	21"	300	EP	
1215020002	4040 EP (1)	4	40"	300	EP	
1215020003	4040 SP - 0°	4	40"	300	SP - 0°	
1215020004	4040 SP - 180°	4	40"	300	SP - 180°	
1215020005	4040 EP (2)	4	2 x 40"	300	EP	
1215020006	4040 EP (3)	4	3 x 40"	300	EP	
1215030001	8040 SP-0° (1)	8	40"	300	SP - 0°	
1215030002	8040 SP-0° (2)	8	2 x 40"	300	SP - 0°	
1215030003	8040 SP-0° (3)	8	3 x 40"	300	SP - 0°	
1215030004	8040 SP-0° (4)	8	4 x 40"	300	SP - 0°	
1215030005	8040 SP-0° (5)	8	5 x 40"	300	SP - 0°	
1215030006	8040 SP-0° (6)	8	6 x 40"	300	SP - 0°	
1318000001	Head Removal Tool					