

SIATA V230

DESCRIPTION

V230 is a commercial valve with the flow rate up to 8.5 m³/h. It's union connections allow an easy installation and maintenance. The valve is suitable for simplex, duplex or multiplex softening systems, as well as for filtration, demineralization, dealkalisation or iron & manganese removal applications and is compatible with the entire SIATA controller range.



FEATURES

- Valve body in ABS material
- Control pressure replicator
- Internal turbine option
- Flow rate is up to 8.5 m³/h
- Compatible with the entire SIATA controller range

VALVE SPECIFICATIONS

Service Flow	8.5 m ³ /h
Backwash Flow Rate	4 m ³ /h
Operating Pressure	1.5 - 6 bar
Valve Material	Glassfiber reinforced ABS
Colours	Blue
Valve Mounting	Top Mounting

VALVE

REFERENCE	SEARCH NAME	ITEM NAME
0302234185	V230F/05	V230 Filter Valve Body Assy
0302234186	V230T/05	V230 Volumetric Valve Body Assy

Top and bottom distributor included, riser tube not included. - Connections must be ordered separately.

Please specify the desired injector and flow controller

ACCESSORIES

REFERENCE	SEARCH NAME	ITEM NAME
0402012695	1005-A/05	V230 Top Distributor (0.3 mm)
0402012697	1006-A/05	V230 Bottom Filter (0.3 mm)
3066000316	RT50	50 mm Riser Tube (per meter) up to 24" Vessels

BLUE VALVES OBSOLETE BY PENTAIR.

ONCE CURRENT STOCKS HAVE BEEN EXHAUSTED BLACK VALVES WILL BE SUPPLIED