

CINTROPUR FILTERS

TRIO-UV CINTROPUR

For the optimal treatment of rain water:

Filters

- Filtration with adapted filters between 5µ and 25µ, depending on you need in order to remove all particles in suspension.

Purifies

- An active carbon treatment against unpleasant smells and tastes in water, as well as the removal of pesticides and herbicides.

Desinfects

- A disinfection of the water thanks to UV that guarantees the bacteriological quality.



Connections	3/4" or 1"
Flow Rate	2m ³ /h (30°C)
Max Operating Pressure	16 bar
Max Temperature	50 °c
Weight	4.3 kg
Water Transmission	Min. 90%
Lamp power	25 W

REFERENCE	ITEM NAME	CONNECTIONS
2514008231	Trio-UV Cintropur	3/4" - 1"

CINTROPUR TIO 1" - UV



Connections	1"
Flow Rate	2m ³ /h (30°C)
Max Operating Pressure	16 bar
Max Temperature	50 °c
Weight	6.2 kg
Water Transmission	Min. 90%
Lamp power	25 W

REFERENCE	ITEM NAME	CONNECTIONS
2514000001	Cintropur TIO 1" - UV	1"

The UV quartz needs to be replaced every 5 years.
The UV lamp needs to be replaced once a year (9000 hours)