

# TESTOMAT® 808

## DESCRIPTION

The Testomat® 808 is a compact analyzer for online measurement of water hardness on the principle of “limit value monitoring with color change”.

- Measurement parameters: water hardness
- Measuring range: 0.02 – 3 °dH water hardness



## APPLICATIONS

- Monitoring the water quality of:
- Reverse osmosis plants
- Soft water for commercial purposes
- Pure water production plants
- Galvanization

## REAGENTS

- Available quantity of indicator:  
100 and 500 ml bottles
- Choose between 10 different limit values

## FEATURES

- Low water consumption
- Cutting-edge electronics
- State-of-the-art indicator pump system
- Error display
- Indicator quantity display
- External flush valve control
- Limit value evaluation / External control
- Alarm processing
- Internal and external flushing via manual control
- 72 hours of unsupervised operation possible
- Choose between interval pause from 0-60 minutes to lower indicator consumption

REFERENCE	ITEM NAME
4801010105	Testomat 808 - Testomat 808 Hardness Monitor 230v
4801010136	Testomat 808 Service Kit
4801010094	Testomat 302 (F-BOB/808) Indicator Fluid 500ml 3.6ppm
4801010092	Testomat 303 (F-BOB/808) Indicator Fluid 500ml 5.4ppm
4801011207	Testomat 305 (F-BOB/808) Indicator Fluid 500ml 9ppm
4801011472	Testomat 310 (F-BOB/808) Indicator Fluid 500ml 18ppm