

TESTOMAT® EVO TH

DESCRIPTION

The Testomat® EVO TH automatically determines the water hardness by titration. It was developed from the Testomat ECO® and will provide you with a lot of new functions additionally to the approved functions which are: integrated SD card, firmware update via SD card and data transmission via WLAN access point and many more.



- Measurement parameters: water hardness
- Measuring range: 0.05 – 25 °dH water hardness
- Application: Universal for water treatment plants
- Menu navigation: German, English, French, Dutch, Spanish, Turkish, Chinese, Czech (others on request)

APPLICATIONS

- Monitoring the water quality of:
- Water treatment
- Water blending
- Drinking-water plants

REAGENTS

- TH2005
- TH2025
- TH2100
- TH2250

FEATURES:

- Optical recognition of water level when filling the measuring chamber
- Import and Export of settings (basic program data) with selectable filenames
- Logging on SD card for measurement data and notifications/alarms or optional SDHC Card (2GByte)
- Firmware update via SD Card
- graphic display (LCD)
- Simple switching between several menu languages
- Built-in self-test with ongoing Monitoring
- External reset / acknowledgment input
- Free programmable Password
- Automatic venting of indicator lines
- Monitoring of exceeding or underrunning of the lower (LV1) and upper limit value (LV2)
- Free programming of permitted number of water shortages (for systems with temporarily low water pressure)

REFERENCE	ITEM NAME	
4801010166	Testomat EVO TH Hardness Monitor 240v50	
4801010159	Yearly Service Kit Testomat 2000 / ECO / EVO	
4801010436	TH2005 - Testomat (ECO/2000) Indicator Fluid 500ml 0.89 - 8.93ppm	
4801011083	TH2025 - Testomat (ECO/2000) Indicator Fluid 500ml 4 - 44.7ppm	
4801014528	TH2100 - Testomat (ECO/2000) Indicator Fluid 500ml 17.9 - 179ppm	
4801010095	TH2250 - Testomat (ECO/2000) Indicator Fluid 500ml 44.8 - 448ppm	